Product Data Sheet

TKE/P 40

Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.

Material cable gland	Polyamide
Material sealing gasket	EPDM
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66, IP68 (5 bar 30 min)
Product Color	RAL 7035
Thread type	M
Ø Connection thread D	40
Lead	1,5
Length screw-in thread L	12 mm
Key width SW	46 mm
Total length TL	52 mm - 65 mm
Glow wire test	750 °C
Type of cable anchorage	A
Install. torques fitting	20 N/m
Install. torques cap nut	20 N/m
Impact category	4
Order no. RAL 7035	10106244
Type	TKE/P 40
Packing unit	1
ETIM-Classification	EC000441

Describtion:

IP 68 Plastic cable gland. ESKV 40/ MFD 2 x 11 mm Tails and 1 x 6 mm Earth. Kit contains insert, locknut and blanking insert.

WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
☎ +49-4191-508-0 · 🖷 +49-4191-508-209
contact@wiska.de · www.wiska.com

Other technical data on request / subject to change without notice

08.05.2018

WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
☎ +49-4191-508-0 · 🖷 +49-4191-508-209
contact@wiska.de · www.wiska.com

Other technical data on request / subject to change without notice