


Comfort LED Downlight

Supplied c/w Remote Driver



- Economic high performance IP44 downlight
- Deep cut-off angle for glare control and comfort
- Osram LED technology and enhanced diffuser design for outstanding uniformity
- Downlight design allows installation into existing hole cut-outs from 200mm to 220mm
- Polycarbonate housing with unique thermal management for durability and optimum lifespan
- LED lifespan L70 50,000 hours
- Dimmable and Emergency options



Powered by
TRIDONIC
enlightening your ideas



LED Information

Total (Watts)	20W	28W
Lumens Delivered		
Cool White	1957lm	2570lm
Warm White	1929lm	2539lm
Lm/W Cool White	100lm	92lm
Lm/W Warm White	101lm	94lm
Beam Angle	55°	
CRI	Ra 80	
CCT	4000K 3000K	
Input	230V	
Hertz	50/60Hz	
Operating Temp	-20°C to 50°C	

Code	Lamp	Description
ACOLED1/CW	LED	20W - Cool White
ACOLED2/CW	LED	28W - Cool White
ACOLED1/WW	LED	20W - Warm White
ACOLED2/WW	LED	28W - Warm White

Options	/M3	Emergency
	/DD	Digital Dimming (DD1/DD2/DD3/DD4)
	DD/M3	Digital Dimming Emergency



Comfort LED HP Downlight


Supplied c/w Remote Driver

68



Powered by
TRIDONIC
enlightening your ideas

- Economic high performance IP44 downlight
- Deep cut-off angle for glare control and comfort
- Osram LED technology and enhanced diffuser design for outstanding uniformity
- Downlight design allows installation into existing hole cut-outs from 200mm to 220mm
- Polycarbonate housing with unique thermal management for durability and optimum lifespan
- LED lifespan L70 50,000 hours
- Dimmable and Emergency options



Code	Lamp	Description
ACOLED3/CW	LED	34W - Cool White
ACOLED3/WW	LED	34W - Warm White

Options		
/M3		Emergency
/DD		Digital Dimming (DD1/DD2/DD3/DD4)
DD/M3		Digital Dimming Emergency

LED Information

Total (Watts)	34W
Lumens Delivered	
Cool White	3830lm
Warm White	3621lm
Lm/W Cool White	112lm
Lm/W Warm White	106lm
Beam Angle	55°
CRI	Ra 80
CCT	4000K
	3000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 50°C

